

Safety data sheet
according to 1907/2006 / EC, Article 31, as amended by Commission
Regulation (EU) No. 2015/830

Printing date 31 May 2021

Version number 12

Revision: 01 March 2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: UAP-11002 Adhesion Promoter**
- **MSDS no. 8,130**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use SU3** Industrial uses: Uses of substances as such or in preparations at industrial sites
- **Application of the substance / the mixture** Printing inks
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
hubergroup Deutschland GmbH
Sonnentallee 1

85551 Kirchheim

Telefon: 089-9003-444
bzw. -390
Telefax: 089-9003-505
- **Informing department:**
Product Safety hubergroup
Telefon: + 49 89-9003-220
Telefax: + 49 89-9003-500
E-mail: product-safety@hubergroup.com
- **1.4 Emergency telephone number:** During general business hours: Product Safety Division, Extension 220 or 375

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



corrosion

Eye Dam. 1 H318 Causes serious eye damage.



environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



STOT SE 3 H336 May cause drowsiness or dizziness.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

— GB —

Safety data sheet
according to 1907/2006 / EC, Article 31, as amended by Commission
Regulation (EU) No. 2015/830

Printing date 31 May 2021

Version number 12

Revision: 01 March 2021

Trade name: **UAP-11002 Adhesion Promoter**

(Contd. of page 1)

· **Hazard pictograms**

GHS02 GHS05 GHS07 GHS09

· **Signal word** Danger· **Hazard-determining components of labelling:**

Butyl alcohol
 Propan-2-ol
 Isobutyl alcohol

· **Hazard statements**

H225 Highly flammable liquid and vapour.
 H318 Causes serious eye damage.
 H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.

· **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P310 Immediately call a POISON CENTER/doctor.
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **2.3 Other hazards** This information is provided by the present Material Safety Data Sheet.· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.
 · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· **3.2 Chemical characterisation: Mixtures**· **Dangerous components:**

	Titanium phosphate complex (polymer)	60-80%
	Flam. Sol. 1, H228; Aquatic Chronic 2, H411; Eye Irrit. 2, H319	
CAS: 67-63-0	Propan-2-ol	20-30%
EINECS: 200-661-7	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	
Reg.nr.: 01-2119457558-25-XXXX		
CAS: 71-36-3	Butyl alcohol	3-<5%
EINECS: 200-751-6	Flam. Liq. 3, H226; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Irrit. 2,	
Reg.nr.: 01-2119484630-38-XXXX	H315; STOT SE 3, H335-H336	
CAS: 78-83-1	Isobutyl alcohol	3-<5%
EINECS: 201-148-0	Flam. Liq. 3, H226; Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3,	
Reg.nr.: 01-2119484609-23-XXXX	H335-H336	

(Contd. on page 3)

— GB —

Safety data sheet
according to 1907/2006 / EC, Article 31, as amended by Commission
Regulation (EU) No. 2015/830

Printing date 31 May 2021

Version number 12

Revision: 01 March 2021

Trade name: UAP-11002 Adhesion Promoter

(Contd. of page 2)

- **Additional information** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures****General information**

In all cases of doubt, or when symptoms persist, seek medical advice.

In case of unconsciousness place person in the recovery position. Never give anything by mouth.

After inhalation

Remove to fresh air.

Keep patient warm and at rest.

After skin contact

Remove contaminated clothing immediately. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

After eye contact

Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart. Remove contact lenses. Obtain medical attention.

After swallowing Do NOT induce vomiting. Obtain medical attention.**4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing agents** Alcohol resistant foam, CO₂, powders, water spray.**For safety reasons unsuitable extinguishing agents** Water jet.**5.2 Special hazards arising from the substance or mixture**

Appropriate breathing apparatus may be required.

Cool closed containers exposed to fire with water.

5.3 Advice for firefighters**Protective equipment:** No special measures required.**Additional information** Collect run-off from fire fighting.**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

Exclude sources of ignition.

Ventilate the area.

Avoid breathing vapours.

6.2 Environmental precautions:

Do not allow to enter drains. If the product contaminates rivers and lakes or sewers inform respective authorities.

6.3 Methods and material for containment and cleaning up:

Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local regulations. Clean preferably with a detergent. Avoid use of solvents.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

(Contd. on page 4)

— GB —

Safety data sheet
according to 1907/2006 / EC, Article 31, as amended by Commission
Regulation (EU) No. 2015/830

Printing date 31 May 2021

Version number 12

Revision: 01 March 2021

Trade name: UAP-11002 Adhesion Promoter

(Contd. of page 3)

See Section 13 for information on disposal.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Prevent the creation of flammable or explosive concentrations of vapour and avoid vapour concentrations higher than the occupational exposure limits.

Additionally, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded.

When transferring from one container to another apply earthing measures and use conductive hose material.

Exercise caution when opening to allow pressure release. Printing ink removed from printing press for storage must be kept in the original container.

No sparking tools should be used.

Avoid inhalation of vapour. Smoking, eating and drinking should be prohibited in application area. For personal protection see Section 8. Comply with health and safety at work laws. Avoid concentrations higher than the occupational exposure limits (see Section 8), if applicable.

Information about protection against explosions and fires:

Vapours may form explosive mixtures with air.

Solvent vapours are heavier than air and may spread along floors.

7.2 Conditions for safe storage, including any incompatibilities**Storage****Requirements to be met by storerooms and containers:**

Storage rooms in which filling operations take place must have a conducting floor.

Never use pressure to empty: container is not a pressure vessel. Keep container tightly closed. Prevent unauthorized access. Opened containers must be carefully resealed and kept upright to prevent leakage.

Keep container tightly closed. No smoking.

Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Further information about storage conditions:

Always keep in containers of the same material as the original one. Store in a dry, well ventilated place. Keep away from heat and direct sunlight. Store in accordance with the particular national regulations concerning water pollution.

Keep away from sources of ignition.

Note Instructions on the label.

7.3 Specific end use(s) No further relevant information available.**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Additional information about design of technical systems:**

If relevant apply technical measures to comply with the occupational exposure limits. This can be by a good general extraction and-if practically feasible, be achieved by local exhaust ventilation.

Components with critical values that require monitoring at the workplace:

Numerical data - if specified - are taken from the valid national lists.

67-63-0 Propan-2-ol (20-30%)

WEL Short-term value: 1250 mg/m³, 500 ppm

Long-term value: 999 mg/m³, 400 ppm

71-36-3 Butyl alcohol (3-<5%)

WEL Short-term value: 154 mg/m³, 50 ppm

Sk

(Contd. on page 5)

— GB —

Safety data sheet
according to 1907/2006 / EC, Article 31, as amended by Commission
Regulation (EU) No. 2015/830

Printing date 31 May 2021

Version number 12

Revision: 01 March 2021

Trade name: UAP-11002 Adhesion Promoter

(Contd. of page 4)

78-83-1 Isobutyl alcohol (3-<5%)WEL Short-term value: 231 mg/m³, 75 ppmLong-term value: 154 mg/m³, 50 ppm**64-17-5 ethanol (1-2.5%)**WEL Long-term value: 1920 mg/m³, 1000 ppm**141-78-6 Ethyl acetate (<1%)**WEL Short-term value: 1468 mg/m³, 400 ppmLong-term value: 734 mg/m³, 200 ppm**· DNELs****67-63-0 Propan-2-ol**

Dermal DNEL workers 888 mg/kg bw/d (human) (chronic; systemic)

Inhalative DNEL workers 500 mg/m³ (human) (chronic; systemic)**71-36-3 Butyl alcohol**Inhalative DNEL workers 310 mg/m³ (human) (chronic; systemic)**· PNECs****67-63-0 Propan-2-ol**

PNEC 28 mg/kg (soil)

PNEC STP 2,251 mg/l (STP)

71-36-3 Butyl alcohol

PNEC 0.015 mg/kg (soil)

PNEC STP 2,476 mg/l (STP)

· 8.2 Exposure controls**· Personal protective equipment****· Breathing equipment:**

The use of respiratory protective measures, such as masks with filters for organic Vapours and dusts / mists are, in the absence of appropriate technical equipment, necessary for the protection of the employee. If exposure is above the exposure limit, then an appropriate, approved respirator must be worn. Please refer to the appropriate EU standard 14387.

· Protection of hands:

For prolonged or repeated contact use gloves.

Barrier creams may help to protect exposed skin, they should however not be applied once have come into contact with the product.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Use safety eyewear designed to protect against splash of liquids.

· Body protection:

Working clothes must not consist of textiles which show a dangerous melting behaviour in case of fire.

All parts of the skin should be washed after contact.

— GB —

(Contd. on page 6)

Safety data sheet
according to 1907/2006 / EC, Article 31, as amended by Commission
Regulation (EU) No. 2015/830

Printing date 31 May 2021

Version number 12

Revision: 01 March 2021

Trade name: UAP-11002 Adhesion Promoter

(Contd. of page 5)

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**
 - **Form:** liquid
 - **Colour:** according to the tradename of the product
- **Smell:** characteristic
- **Odour threshold:** Not determined.
- **pH-value:** Not determined.
- **Change in condition**
 - **Melting point/freezing point:** not determined
- **Flash point:** 15 °C
- **Inflammability (solid, gaseous)** Not applicable.
- **Decomposition temperature:** Not determined.
- **Self-inflammability:** Not determined.
- **Explosive properties:** Not determined.
- **Critical values for explosion:**
 - **Lower: approx.** 2 Vol %
 - **Upper: approx.** 12 Vol %
- **Vapour pressure:** Not determined.
- **Density at 20 °C** 0.913 g/cm³
- **Relative density** Not determined.
- **Vapour density** Not determined.
- **Evaporation rate** Not applicable.
- **Solubility in / Miscibility with**
 - **Water:** partly or not miscible
- **Partition coefficient: n-octanol/water:** Not determined.
- **Viscosity:**
 - **dynamic:** Not determined.
 - **kinematic:** Not determined.
- **Solvent separation test**
 - **Organic solvents:** 30-50 %
 - **Solid content:** 64.0 %
- **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability** No further relevant information available.
- **10.3 Thermal decomposition / conditions to be avoided:**
Stable under recommended storage and handling conditions (see section 7).
- **10.4 Conditions to avoid** No further relevant information available.

(Contd. on page 7)

— GB —

Safety data sheet
according to 1907/2006 / EC, Article 31, as amended by Commission
Regulation (EU) No. 2015/830

Printing date 31 May 2021

Version number 12

Revision: 01 March 2021

Trade name: UAP-11002 Adhesion Promoter

(Contd. of page 6)

10.5 Incompatible materials:

Keep well away from oxidising agents and strongly alkaline or strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products:

Exposition to high temperatures may produce hazardous decomposition products such as: carbon dioxide, carbon monoxide and smoke.

SECTION 11: Toxicological information

The Preparation is classified according to the conventional method (calculation method of the CLP Regulation (EC) No 1272/2008).Liquid splashes, get the eye can cause permanent damage. The eye must be flushed out immediately. Medical attention.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis.

The liquid splashed in the eyes may cause strong irritation and reversible damage.

11.1 Information on toxicological effects

· **Acute toxicity** Based on available data, the classification criteria are not met.

LD/LC50 values that are relevant for classification:**67-63-0 Propan-2-ol**

Oral LD50 5,280 mg/kg (rat)

Dermal LD50 13,900 mg/kg (rabbit)

Inhalative LC50 >25,000 mg/m³ (rat) (6 h)

71-36-3 Butyl alcohol

Oral LD50 2,292 mg/kg (rat)

Dermal LD50 3,400 mg/kg (rbt)

Inhalative LC50 >17,000 mg/m³ (rat)

78-83-1 Isobutyl alcohol

Oral LD50 2,460 mg/kg (rat)

Dermal LD50 4,200 mg/kg (rbt)

Specific symptoms in biological assay:

· **Skin corrosion/irritation** Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Causes serious eye damage.

· **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

Additional toxicological information:

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

· **Germ cell mutagenicity** Based on available data, the classification criteria are not met.

· **Carcinogenicity** Based on available data, the classification criteria are not met.

· **Reproductive toxicity** Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

· **STOT-repeated exposure** Based on available data, the classification criteria are not met.

(Contd. on page 8)

Safety data sheet
according to 1907/2006 / EC, Article 31, as amended by Commission
Regulation (EU) No. 2015/830

Printing date 31 May 2021

Version number 12

Revision: 01 March 2021

Trade name: **UAP-11002 Adhesion Promoter**

(Contd. of page 7)

- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

The Product should not be allowed to enter drains of water courses or soil.

- **12.1 Toxicity**

- **Aquatic toxicity:**

- **67-63-0 Propan-2-ol**

- Fish toxicity 9,640 mg/l (fish) (LC50 96h)

- Daphnia toxicity 9,714 mg/l (daphnia) (LC50; 24h)

- Algae toxicity >100 mg/l (algae) (EC50; 72h)

- **71-36-3 Butyl alcohol**

- Fish toxicity 1,376 mg/l (fish) (LC50; 96 h)

- Daphnia toxicity 1,328 mg/l (daphnia) (EC50; 48 h)

- Algae toxicity 225 mg/l (algae) (EC50; 96 h)

- **12.2 Persistence and degradability** No further relevant information available.

- **12.3 Bioaccumulative potential** No further relevant information available.

- **12.4 Mobility in soil** No further relevant information available.

- **Ecotoxicological effects:**

- **Remark:** Toxic for fish

- **Additional ecological information:**

- **General notes:** Toxic for aquatic organisms

- **12.5 Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**

- **Recommendation** Do not allow to enter drains.

- **Uncleaned packagings:** Waste

- **Recommendation:**

Emptied containers should be disposed off into scrap recycling or reconditioning respectively.

Not orderly emptied cans and ink remnants are special waste.

SECTION 14: Transport information

Transport only in accordance with ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport.

- **14.1 UN-Number**

- **ADR, IMDG, IATA**

UN1263

- **14.2 UN proper shipping name**

- **ADR**

1263 PAINT RELATED MATERIAL, ENVIRONMENTALLY HAZARDOUS

- **IMDG**

PAINT RELATED MATERIAL (Titanium phosphate complex (polymer)), MARINE POLLUTANT

(Contd. on page 9)

Safety data sheet
 according to 1907/2006 / EC, Article 31, as amended by Commission
 Regulation (EU) No. 2015/830

Printing date 31 May 2021

Version number 12

Revision: 01 March 2021

Trade name: UAP-11002 Adhesion Promoter

(Contd. of page 8)

· IATA PAINT RELATED MATERIAL
 · 14.3 Transport hazard class(es)

· ADR



· Class 3 (F1) Flammable liquids.
 · Label 3

· IMDG



· Class 3 Flammable liquids.
 · Label 3

· IATA



· Class 3 Flammable liquids.
 · Label 3
 · 14.4 Packing group II
 · ADR, IMDG, IATA II
 · 14.5 Environmental hazards: Yes
 · Marine pollutant: Symbol (fish and tree)
 · Special marking (ADR): Symbol (fish and tree)
 · 14.6 Special precautions for user Warning: Flammable liquids.
 · Kemler Number: 33
 · EMS Number: F-E, S-E
 · Stowage Category B
 · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.

· Transport/Additional information:

· ADR
 · Excepted quantities (EQ): E2
 · Limited quantities (LQ) 5L
 · Excepted quantities (EQ) Code: E2
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 500 ml
 · Transport category 2
 · Tunnel restriction code D/E

(Contd. on page 10)

Safety data sheet
according to 1907/2006 / EC, Article 31, as amended by Commission
Regulation (EU) No. 2015/830

Printing date 31 May 2021

Version number 12

Revision: 01 March 2021

Trade name: **UAP-11002 Adhesion Promoter**

(Contd. of page 9)

<ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) · UN "Model Regulation": 	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml UN 1263 PAINT RELATED MATERIAL, 3, II, ENVIRONMENTALLY HAZARDOUS
---	--

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **National regulations**
The product is subject to classification in accordance with the prevailing version of the regulations on hazardous materials.
- **Information about limitation of use:**
- **VOC-Content (EU):** 36.00 %
- **Other regulations, limitations and prohibitive regulations**
- **Swiss VOC-Regulation** 36.00 %
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

The information on this Safety Data Sheet is based on the present state of our knowledge and on current EU and national laws. The user's working conditions are beyond our knowledge and control. It is always the responsibility of the user to take all necessary steps in order to fulfil the demands laid down in the local rules and legislation. The information in this Safety Data Sheet is meant as a description of the safety requirements of our product: it is not to be considered as a guarantee of the product's properties.

- **Relevant phrases**
 H225 Highly flammable liquid and vapour.
 H226 Flammable liquid and vapour.
 H228 Flammable solid.
 H302 Harmful if swallowed.
 H315 Causes skin irritation.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.
- **Abbreviations and acronyms:**
 ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances

(Contd. on page 11)

— GB —

Safety data sheet
according to 1907/2006 / EC, Article 31, as amended by Commission
Regulation (EU) No. 2015/830

Printing date 31 May 2021

Version number 12

Revision: 01 March 2021

Trade name: UAP-11002 Adhesion Promoter

(Contd. of page 10)

CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Flam. Sol. 1: Flammable solids – Category 1
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

GB
