



# IMA S.R.L. **IMAPUR 1515/25 HR**

Revision nr 5 Dated 1/6/2015 Printed on 1/6/2015 Page n. 1/9

PV

# Safety data sheet

# SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name **IMAPUR 1515/25 HR** 

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Solvent-based aliphatic polyurethane finish

1.3. Details of the supplier of the safety data sheet

IMA S.R.L. Name Full address Via Segrè, 23 27036 Mortara

District and Country

0039.0384 29.73.11 Tel. Fax 0039.0384 29.67.32

e-mail address of the competent person

responsible for the Safety Data Sheet RD.lab@imadelta.com

1.4. Emergency telephone number

For urgent inquiries refer to 0039.0384/297311 (orario d'ufficio) 0039.0384/297311 (office hours)

# **SECTION 2. Hazards identification**

# 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

# 2.1.1. Regulation 1272/2008 (CLP) and following amendments and adjustments

Hazard classification and indication:

Flam. Liq. 3 Repr. 1B H360D H312+H332 Acute Tox. 4 Eye Irrit. 2 H319

## 2.1.2. 67/548/EEC and 1999/45/EC Directives and following amendments and adjustments.

Danger Symbols:

20/21-36-61 R phrases: Repr.Cat.2

The full wording of the Risk (R) and hazard (H) phrases is given in section 16 of the sheet

#### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:









# IMA S.R.L. IMAPUR 1515/25 HR

Revision nr.5 Dated 1/6/2015 Printed on 1/6/2015 Page n. 2 / 9

SECTION 2. Hazards identification .../>>

Signal words: Danger

Hazard statements:

H226 Flammable liquid and vapour. H360D May damage the unborn child.

H312+H332 Harmful in contact with skin or if inhaled.

H319 Causes serious eye irritation.
Restricted to professional users.

Precautionary statements:

**P201** Obtain special instructions before use.

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P280 Wear protective gloves / protective clothing / eye protection / face protection.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P370+P378 In case of fire: Use . . . for extinction.

Contains: DIMETHYL FORMAMIDE

#### 2.3. Other hazards

Information not available

# SECTION 3. Composition/information on ingredients

### 3.1. Substances

Information not relevant

#### 3.2. Mixtures

Contains:

Identification Conc. % Classification 67/548/EEC Classification 1272/2008 (CLP)

**DIMETHYL FORMAMIDE** 

CAS 68-12-2 73 - 78 Repr. Cat. 2 R61, Xi R36, Xn R20/21 Flam. Liq. 3 H226, Repr. 1B H360D, Acute Tox. 4 H312, Acute Tox. 4 H332, Eye Irrit. 2 H319, Nota E

EC 200-679-5 INDEX 616-001-00-X

Reg. no. 01-2119475605-32-xxxx

reg. 110. 01-2119+10000-02-XXXX

T= TOXIC,Xi= IRRITANT,Xn= HARMFUL

Note: Upper limit is not included into the range

The full wording of the Risk (R) and hazard (H) phrases is given in section 16 of the sheet

# **SECTION 4. First aid measures**

### 4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

# 4.2. Most important symptoms and effects, both acute and delayed

For symptoms and effects caused by the contained substances, see chap. 11.

## 4.3. Indication of any immediate medical attention and special treatment needed

Information not available



# IMA S.R.L. IMAPUR 1515/25 HR

Revision nr.5 Dated 1/6/2015 Printed on 1/6/2015 Page n. 3 / 9

# **SECTION 5. Firefighting measures**

#### 5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

# 5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

#### 5.3. Advice for firefighters

**GENERAL INFORMATION** 

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

#### **SECTION 6. Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

Send away individuals who are not suitably equipped. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

# 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

# 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

# 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

# **SECTION 7. Handling and storage**

#### 7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

# 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

# 7.3. Specific end use(s)

Information not available



# IMA S.R.L. **IMAPUR 1515/25 HR**

Revision nr 5 Dated 1/6/2015 Printed on 1/6/2015 Page n. 4/9

# SECTION 8. Exposure controls/personal protection

#### 8.1. Control parameters

Éire

OEL EU

Regulatory References:

United Kingdom EH40/2005 Workplace exposure limits. Containing the list of workplace exposure limits

for use with the Control of Substances Hazardous to Health Regulations (as amended).

Code of Practice Chemical Agent Regulations 2011.

Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive

2000/39/FC

**TLV-ACGIH ACGIH 2012** 

				DIMETHYL	<b>FORMAN</b>	MIDE
Threshold Limit Value						
Type	Country	TWA/8h		STEL/15r	STEL/15min	
		mg/m3	ppm	mg/m3	ppm	
WEL	UK	15	5	30	10	SKIN
OEL	IRL	15	5	30	10	SKIN
OEL	EU	15	5	30	10	SKIN
TLV-ACGIH		30	10			

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

#### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

### HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

#### SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

# **EYE PROTECTION**

Wear airtight protective goggles (see standard EN 166).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

#### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529. **ENVIRONMENTAL EXPOSURE CONTROLS** 

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.



Flammability (solid, gas)

Lower inflammability limit

Upper inflammability limit

# IMA S.R.L. IMAPUR 1515/25 HR

Not available

Not available Not available

Not available

Revision nr.5 Dated 1/6/2015 Printed on 1/6/2015 Page n. 5 / 9

# **SECTION 9. Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Appearance Viscous liquid

Colour Colourless or slightly yellow

Odour Characteristic Odour threshold Not available Not available Melting point / freezing point Not available Initial boiling point 153 °C 151-155°C Boiling range Flash point > 56 °C **Evaporation Rate** 0,20

Lower explosive limit Not available Upper explosive limit Not available Not available Vapour pressure Vapour density Not available Not available Relative density Solubility Insoluble in water Partition coefficient: n-octanol/water Not available Not available Auto-ignition temperature Decomposition temperature Not available Viscosity 15000-30000 mPa.s Not available Explosive properties

# 9.2. Other information

Oxidising properties

VOC (Directive 1999/13/EC) : 74,93% VOC (volatile carbon) : 36,91%

# **SECTION 10. Stability and reactivity**

### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

DIMETHYL FORMAMIDE:decomposes on contact with flames and hot surfaces to generate toxic fumes.

#### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

## 10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

DIMETHYL FORMAMIDE: risk of explosion on contact with: alkaline metals, strong oxidising agents, bromine, chlorine, triethyl aluminium, alkaline nitrides. Can react violently with: reducing agents, halogens, nitrates, metal and non-metal oxides, halogenated hydrocarbons. Forms explosive mixtures with air when warm.

# 10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

DIMETHYL FORMAMIDE: avoid exposure to sources of heat and naked flames.

#### 10.5. Incompatible materials

DIMETHYL FORMAMIDE: oxidising substances, halogenated hydrocarbons, inorganic nitrates, triethyl aluminium, bromine, chlorine and iron.

# 10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

DIMETHYL FORMAMIDE: nitric oxides, dimethylamine, hydrogen cyanide.

# **SECTION 11. Toxicological information**

# 11.1. Information on toxicological effects

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

# THE WORLD OF FARRIC COATING

# IMA S.R.L. IMAPUR 1515/25 HR

Revision nr.5 Dated 1/6/2015 Printed on 1/6/2015 Page n. 6 / 9

# SECTION 11. Toxicological information />>

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

This product has a teratogenic effect on human beings; it has toxic effects on fetus development.

There is sufficient evidence to make us believe that the substance contained in the product is likely to affect the embryo-fetal development

Acute effects: inhalation and cutaneous absorption of this product are harmful. This product may irritate mucosas, the upper respiratory tract, and eyes. Exposure symptoms may include: stinging and irritated eyes, mouth, nose, throat; cough, respiratory disorders, dizziness, headache, nausea and sickness.

In the most serious cases, inhalation of this product may cause larynx and bronchial tube edema and irritation, chemical pneumonia and pulmonary edema. Upon contact with skin, this product may irritate it, causing an increase in skin temperature, swelling and itchiness. Ingestion of even small amounts of this product may cause health problems (stomach pain, nausea, sickness, diarrhoea).

Acute effects: stinging eyes. Symptoms may include: rubescence, edema, pain and lachrymation.

Vapour inhalation may moderately irritate the upper respiratory trait. Contact with skin may cause slight irritation.

Ingestion may cause health problems, including stomach pain and sting, nausea and sickness.

DIMETHYL FORMAMIDE

LD50 (Oral) 2.800 mg/kg Rat LC50 (Inhalation) >5,9 mg/l/4h Rat

# **SECTION 12. Ecological information**

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or sewers or contaminate soil or vegetation.

#### 12.1. Toxicity

Information not available

#### 12.2. Persistence and degradability

The product is not biologically decomposable.

### 12.3. Bioaccumulative potential

Information not available

# 12.4. Mobility in soil

Information not available

# 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

#### 12.6. Other adverse effects

Information not available

# **SECTION 13. Disposal considerations**

# 13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Avoid littering. Do not contaminate soil, sewers and waterways.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

# **SECTION 14. Transport information**

These goods must be transported by vehicles authorized to the carriage of dangerous goods according to the provisions set out in the current edition of the Code of International Carriage of Dangerous Goods by Road (ADR) and in all the applicable national regulations. These goods must be packed in their original packagings or in packagings made of materials resistant to their content and not reacting dangerously with it. People loading and unloading dangerous goods must be trained on all the risks deriving from these substances and on all actions that must be taken in case of emergency situations.



# IMA S.R.L.

# **IMAPUR 1515/25 HR**

Revision nr.5 Dated 1/6/2015 Printed on 1/6/2015 Page n. 7 / 9

# SECTION 14. Transport information ..../>>

Road and rail transport:

ADR/RID Class: 3 UN: 1866

Packing Group: III
Label: 3
Nr. Kemler: 30
Special Provision: 640E
Limited Quantity 5 L
Tunnel restriction code D/E



Proper Shipping Name: Resin solution

Carriage by sea (shipping):

IMO Class: 3 UN: 1866

 Packing Group:
 III

 Label:
 3

 EMS:
 F-E, S-E

 Marine Pollutant
 NO

Proper Shipping Name: Resin solution

Transport by air:

IATA: 3 UN: 1866

Packing Group: III Label: 3

Cargo:

Packaging instructions: 366 Maximum quantity:

Pass.:

Packaging instructions: 355 Maximum quantity: 60 L

Proper Shipping Name: Resin solution

# **SECTION 15. Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso category

None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3-40

Contained substance

Point 30 DIMETHYL FORMAMIDE

Substances in Candidate List (Art. 59 REACH)

DIMETHYL FORMAMIDE

Substances subject to authorisarion (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

# 15.2. Chemical safety assessment

No chemical safety assessment has been processed for the mixture and the substances it contains.



# IMA S.R.L. IMAPUR 1515/25 HR

Revision nr.5 Dated 1/6/2015 Printed on 1/6/2015 Page n. 8 / 9

# **SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 3

Repr. 1B

Acute Tox. 4

Eye Irrit. 2

H226

H360D

H312

Flammable liquid, category 3

Reproductive toxicity, category 1B

Acute toxicity, category 4

Eye irritation, category 2

Flammable liquid and vapour.

May damage the unborn child.

Harmful in contact with skin.

H312+H332 Harmful in contact with skin or if inhaled.
H332 Harmful if inhaled.

H319 Causes serious eye irritation.

Text of risk (R) phrases mentioned in section 2-3 of the sheet:

Repr.Cat. 2 Reproductive toxicity, development, category 2

R20/21 HARMFUL BY INHALATION AND IN CONTACT WITH SKIN.

R36 IRRITATING TO EYES.

R61 MAY CAUSE HARM TO THE UNBORN CHILD.

#### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

# **GENERAL BIBLIOGRAPHY**

- 1. Directive 1999/45/EC and following amendments
- 2. Directive 67/548/EEC and following amendments and adjustments
- 3. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 4. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 5. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 6. Regulation (EC) 453/2010 of the European Parliament
- 7. Regulation (EC) 286/2011 (II Atp. CLP) of the European Parliament
- 8. Regulation (EC) 618/2012 (III Atp. CLP) of the European Parliament
- 9. The Merck Index. 10th Edition
- 10. Handling Chemical Safety



# IMA S.R.L. IMAPUR 1515/25 HR

Revision nr.5 Dated 1/6/2015 Printed on 1/6/2015 Page n. 9 / 9

# SECTION 16. Other information .../>>

- 11. Niosh Registry of Toxic Effects of Chemical Substances
- 12. INRS Fiche Toxicologique (toxicological sheet)
- 13. Patty Industrial Hygiene and Toxicology
- 14. N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- 15. ECHA website

#### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:

The following sections were modified: 01/02/03/04/05/06/07/08/09/10/11/12/13/14/15/16