

DESCRIPTION	Aromatic one-component PU resin. Polyester based. In solvent mixture. Medium-soft hand. Good adhesion to plasticized PVC.	
USE	Adhesive for PU and PU/PVC articles to be used when a medium-soft hand is required.	
Characteristics of the product	<i>Aspect:</i>	Viscous liquid
	<i>Dry Content:</i>	35,00%± 1
	<i>Solvent/s</i>	DMF/TOL
	<i>Viscosity (25 °C)</i>	20.000 - 40.000 mPa.s
Physical characteristics of the dry film	<i>Modulus 100% (Kg/cm2):</i>	40
	<i>Modulus 300% (Kg/cm2):</i>	110
	<i>Tensile Stenght(Kg/cm2):</i>	345
	<i>Elongation(%):</i>	730
	<i>T.Kofler (softening) (°C):</i>	160
	<i>T.Kofler (melting point)(°C):</i>	170
Modifiers	<i>For dilution</i>	DMF, DMF/TOL(MIX)
	<i>For the pigmentation</i>	NOVA TC ND
	<i>For the colouring</i>	IMACOLOR
Packing	<i>Metal drums of Kgs:</i>	200
Storage	The product must be stored at temperatures between -1 °C and 30 °C. In this conditions the product is stable for 6 months	
Notes	KEEP PACKINGS PERFECTLY SEALED SHELTER FROM MOISTURE	

Legend	N.A. = NOT APPLIABLE	N.D. = NON DETERMINED	F.C. = FORD CUP
<i>First issuing date:</i>	19/04/2000	<i>Revision date:</i>	23/02/2021
		<i>Revision nr.:</i>	7
		<i>Print date:</i>	15/02/2023