

Description

UHVM-24703 is a reactive diluent for energy curing systems.

Characteristics

- Hardness
- Good adhesion to plastics
- Chemical resistance
- High reactivity

Suggested Application

- Flexo inks
- Screen inks
- 3D printing
- Metal coatings
- Plastic coatings
- Wood coatings

Typical Properties

Acid value [mg KOH/g]	≤ 0.5
Appearance	clear liquid
Colour, APHA	≤ 30
Double bond density [mol/kg]	7.8-8.5
Solvent content [%]	< 0.1
Moisture content [%]	< 0.1
Viscosity @ 25 °C, Brookfield [mPa·s]	5 - 30
Density [g/cm ³]	Approx. 1.0006

Storage

The product should be stored in a cool, dry place in unopened original packaging and should not be exposed to direct sunlight. Typical storage temperatures should be between 15 - 30 °C.

Shelf Life

The product has a shelf life of at least 12 months from the date of manufacture.

Safety

When handling this product, please work according to the advice and information given in the safety data sheet and observe protective and workplace hygiene measures adequate for handling chemicals.

Packaging

200 kg drums
1000 kg IBC

Disclaimer

This product is currently in scale-up. Samples are from pilot production.

 chemicals@hubergroup.com

This Technical Data Sheet can only be of an advisory nature. Our data reflect the latest state of our knowledge and are based on the characteristics established in the laboratory and on practical experience. Because there are many factors under the control of the user which may affect processing or application/use, it is necessary for the user to carry out appropriate tests to determine whether the product is technically and safely suitable for the particular purpose, prior to use. No warranties of any kind, either expressed or implied, are made regarding the product here described. We assume no liability for correctness.